



H.264 DVR CS-D5504AN



■ Features

- ◆ H264 standard compression format with efficient processing and clear image
- ◆ Support CIF/D1 recording encoding
- ◆ Two high-speed USB2.0 interfaces, you can mix backup and mouse
- ◆ Support six operations at the same time, recording, playback, network transmission, backup, mobile monitoring, PTZ control etc
- ◆ Support IE and client, remote parameter settings / convenient remote network access function without need to apply for any domain names, plug and play
- ◆ Dedicated high-reliability file system for special monitoring
- ◆ Simplified Chinese, English, Thai, Russian, French, Spanish etc. over twenty languages
- ◆ A powerful mobile control and monitoring features to support Window Mobile, Symbian, Android, iPhone and Blackberry etc

Specifications

Model Name	CS-D5504AN		
System	Main Processor	DVR 4ch (Hybrid)	
	System Resource	Sixfold operation: Live recording, Playback, Backup, Remote access, PTZ control, Mobile monitoring	
	Control Mode	USB mouse, Network	
Video	Input	4×BNC, (1.0Vp-p, 75Ω)	
	Standard	4ch +4CH CIF real time , NTSC:240FPS, PAL:200FPS	
	Output	1×BNC, (1.0Vp-p, 75Ω), 1×VGA	
Audio	Input	1×RCA	
	Output	1×RCA	
Display	Display Split	1/4/8/9	
	Resolution	VGA:1920*1080, 1280*1024, 1024*768, 800*600	
	Tour Display	Support	
Recording	OSD	Camera title, Time, Video loss, Motion detection, Recording	
	Video/Audio	H.264/ADPCM	
	Image Resolution	5 mp (1080)	
	Performance	4D1 + 4CIF	
	Encoding stream	Main stream	D1: 100fps@PAL、120fps@NTSC
		Extra	CIF:20FPS
	Recording Mode	Manual, schedule, Motion detection, Alarm	
Recording Priority	Manual>Alarm>Motion detection		
Video detection & Alarm	Trigger events	Recording, PTZ movement, Alarm, E-mail	
	Motion detection	Zones:396 (22*18) , Sensitivity:1-5 (Level 5 is the highest)	
	Video loss	Support	
	Alarm	None	
Playback & Backup	Playback channel	4D1	
	Playback speed	D1: 50fps@PAL、60fps@NTSC, CIF:200fps@PAL、240fps@NTSC	
	Search mode	Time/date, Alarm, Motion detection	
	Playback function	Play, Pause, Stop, Fast forward, Slow forward, Full screen etc. Recording files can be viewed by dragging the progress bar back and forth	
	Backup mode	U-disk /USB-HDD/USB-CD /Network	
Network	Physical interface	RJ-45port(10/100M)	
	Network function	TCP/IP, UDP, DHCP, DNS, IP filter, PPPOE, E-mail, Alarm server, UPNP, DDNS, DNS Binding	
	Remote operation	Monitor, PTZ control, Playback, System setting, files download, Log information	
	Mobile Phone	Support Window Mobile, Symbian, Android, iPhone, Blackberry etc.	
Hard Disk	Hard disk	1 SATA port, the capacity of single hard disk MAX 2T	
	Space occupation	Audio: 14.4MB/H, Video: 56-900MB/H	
	HDD management	Hard disk hibernation technology, HDD faulty alarm, file restoration	
Auxiliary Interface	USB	Two USB2.0 interface, for connecting mouse, U-disk, USB hard disk	
	RS485	PTZ control	
Environment	Power supply	12V/3A	
	Working environment	-10℃~+55℃/10~90%RH/86~106Kpa	
	Dimension	250*235*45mm(Product size)	
	Weight	2.0kg(W/O HDD); Package Weight:2.8Kg	

Design and specifications are subject to change without notice.